

## RefLED ES50 V3


RefLED ES50 V3 345lm DIM 830 36° SL

**0027440**



### Product features

- Good every day quality from a brand you can trust. RefLED ES50 V3 Dimmable delivers a cost effective solution to replacing halogen GU10 with LED offering 345lm of light equivalent to a 50W halogen lamp while extending lamp life to 15,000 hours. GU10 cap. 36 degree beam angle in Warm white 3000K. Backed by a 3 year warranty. CCSMD Technology delivers a halogen look lens with high efficiency and good thermal control.



### PRODUCT OVERVIEW

Product code	0027440
Product name	RefLED ES50 V3 345lm DIM 830 36° SL
Technology	LED
Watt (Rated) (W)	5.5
Lamp shape	GU10/ES50
Cap/Base	GU10
Lamp finish	White
General application	Hospitality, Residential & Consumer
Certifications	EUTIE105
ETIM Class	EC001959
E-number Finland	4740466
E-number Sweden	8292497
Luminous flux (lm)	345
Efficacy (lm/w)	62.73
Colour temperature (K)	3000
Light colour	830 Warm White
Colour Consistency (SDCM)	6
Wattage (W)	5.5
Average life (Nominal) (h)	15000
Product EAN number	5410288274409
Chromaticity coordinate Y	0.404

### DATA TABLE

#### General data

Product code	0027440
Product name	RefLED ES50 V3 345lm DIM 830 36° SL
Technology	LED
Watt (Rated) (W)	5.5

## RefLED ES50 V3

RefLED ES50 V3 345lm DIM 830 36° SL

**0027440**

<b>Lamp shape</b>	GU10/ES50
<b>Cap/Base</b>	GU10
<b>Lamp finish</b>	White
<b>General application</b>	Hospitality, Residential & Consumer
<b>Certifications</b>	EUTIE105
<b>ETIM Class</b>	EC001959
<b>E-number Finland</b>	4740466
<b>E-number Sweden</b>	8292497

### Optical data

<b>Luminous flux (lm)</b>	345
<b>Luminous flux (Rated) (lm)</b>	345
<b>Efficacy (lm/w)</b>	62.73
<b>Colour temperature (K)</b>	3000
<b>Correlated colour temperature range (K)</b>	3000
<b>Light colour</b>	830 Warm White
<b>Colour Consistency (SDCM)</b>	6
<b>Adjustable chromaticity</b>	N
<b>Beam angle (Rated) (°)</b>	36
<b>Lumen maintenance at end of nominal life (%)</b>	70

### Electrical data

<b>Wattage (W)</b>	5.5
<b>Equivalent watt (W)</b>	50
<b>Starting time (max) (s)</b>	<0.5
<b>Warm-up time to 60% of full light (max) (s)</b>	< 2s => 95%
<b>Current (A)</b>	0.032
<b>Mains voltage (V)</b>	220-240V~
<b>Lamp power factor</b>	0.5
<b>Mains frequency (Hz)</b>	50
<b>Control gear required</b>	No
<b>No. Of switching cycles before premature failures</b>	50000
<b>Transformer required</b>	No
<b>Inrush Current (A)</b>	0.32
<b>Lamp Energy Label (class)</b>	A+
<b>Energy efficiency level</b>	A+
<b>kWh per 1000 hours burning time</b>	6

### Lifetime data

<b>Average life (Nominal) (h)</b>	15000
-----------------------------------	-------

## RefLED ES50 V3

RefLED ES50 V3 345lm DIM 830 36° SL

**0027440**

**Average life (Rated) (h)** 15000

### Physical data

<b>Max. Lamp Diameter (mm) - D</b>	50
<b>Weight (kg)</b>	0.038

### Packaging

<b>Single packaging type</b>	Carton
<b>Product EAN number</b>	5410288274409
<b>Packaging single length (cm)</b>	5.2
<b>Packaging single width (cm)</b>	5.2
<b>Packaging single height (cm)</b>	6.1
<b>DUN14 (inner)</b>	25410288274403
<b>Units per inner package</b>	6
<b>Packaging inner length (cm)</b>	7.5
<b>Packaging inner width (cm)</b>	11.6
<b>Packaging inner height (cm)</b>	16.7
<b>DUN14 (outer)</b>	15410288274406
<b>Units per outer package</b>	60
<b>Packaging outer length (cm)</b>	59.8
<b>Packaging outer width (cm)</b>	18.7
<b>Packaging outer height (cm)</b>	17.1

### Safety data

<b>Breakage cleaning instructions</b>	Not applicable
<b>Recommendation for disposal at end of life</b>	Not applicable
<b>Special purpose lamp</b>	No
<b>Intended purpose</b>	General lighting
<b>Suitable for household illumination</b>	No
<b>Suitable for accent lighting</b>	Yes
<b>Safety message</b>	Suitable for totally enclosed fixture

## RefLED ES50 V3

RefLED ES50 V3 345lm DIM 830 36° SL

**0027440**

