

ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 4FT 2400LM 840

0029505



Product features

- 60,000 hours average rated lifetime (L70 F50)• Last 3 times longer than 28W 1149mm fluorescent tri-phosphor T5 lamp. • High switching cycles – 200,000X• High lumen efficacy -150lm/W• Omni-directional light distribution and wide beam angle• Minimum and maximum operating temperature: -20°C to 50°C• Glass construction and polycarbonate end-caps• Not suitable for direct mains (AC 220-240V) or magnetic/ CCG ballast• Works only with compatible electronic ballasts. • Ideal for factories, parking lots, supermarkets, department stores, schools and offices.



PRODUCT OVERVIEW

Product code	0029505
Product name	TOLEDO SUPERIA T5 HE 4FT 2400LM 840
Technology	LED
Watt (Rated) (W)	16
General application	Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries,
Certifications	EUERL010
ETIM Class	EC001959
E-number Finland	4740602
Luminous flux (lm)	2400
Colour temperature (K)	4000
Light colour	4000 Cool White
CRI (Ra)	80
Wattage (W)	16
Product Voltage (V)	80
Average life (Nominal) (h)	60000
Product EAN number	5410288295053

DATA TABLE

General data

Product code	0029505
Product name	TOLEDO SUPERIA T5 HE 4FT 2400LM 840
Technology	LED
Watt (Rated) (W)	16
General application	Office, Hospitality, Retail, Logistics & Industry, Education, Residential & Consumer, Museums & Galleries,
Operating Temperature Range (°C)	25
Certifications	EUERL010
ETIM Class	EC001959

ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 4FT 2400LM 840

0029505

E-number Finland	4740602
-------------------------	---------

Optical data

Luminous flux (lm)	2400
Luminous flux (Rated) (lm)	2400
Colour temperature (K)	4000
Light colour	4000 Cool White
CRI (Ra)	80
Beam angle (Rated) (°)	220
Lumen maintenance at end of nominal life (%)	70

Electrical data

Wattage (W)	16
Watt (Rated) - High frequency (W)	16
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	<2
Current (A)	0.24
Product Voltage (V)	80
Lamp power factor	0.89
No. Of switching cycles before premature failures	200000
Lamp Energy Label (class)	A++
kWh per 1000 hours burning time	18

Lifetime data

Average life (Nominal) (h)	60000
Average life (Rated) (h)	60000

Physical data

Weight (kg)	0.148
--------------------	-------

Packaging

Single packaging type	Carton
Product EAN number	5410288295053
Packaging single length (cm)	1.8
Packaging single width (cm)	1.8
Packaging single height (cm)	116.5
DUN14 (outer)	15410288295050
Units per outer package	10
Packaging outer length (cm)	122.0
Packaging outer width (cm)	15.5

ToLEDo Superia Tube T5

TOLEDO SUPERIA T5 HE 4FT 2400LM 840

0029505

Packaging outer height (cm) 8.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Suitable for household illumination	Yes
Safety message	Suitable for totally enclosed fixture

