

ToLEDo Vintage CANDLE

TOLEDO™ VINTAGE CANDLE 125LM E27 SL

0027972



Product features

- New and innovative Flexible Filament Chip Technology (FFCT) designed to create the low-lit vintage effect.
- Perfect for hotels, restaurants, heritage lighting, bars and decorative applications.
- The ideal LED solution to replace incandescent vintage candle lamp.
- Low glare – suitable for low height installation.
- 2000K colour temperature, to create a cosy ambience.
- Golden tinted glass envelope.
- 15,000 hours average rated life. Last 7.5 times longer than incandescent vintage lamps.
- Unique filament construction design – 'Cord' shape.
- Omni-directional light distribution – 300°.
- Low-lumen output to create low-lit effect – 125lm.
- More than 100,000X switching cycles.
- 3 years warranty.
- Environment friendly – no mercury and lower CO2 emissions.



PRODUCT OVERVIEW

Product code	0027972
Product name	TOLEDO™ VINTAGE CANDLE 125LM E27 SL
Technology	LED
Watt (Rated) (W)	2.3
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer,
Certifications	EUTIE103
ETIM Class	EC001959
Luminous flux (lm)	125
Colour temperature (K)	2000
Light colour	Candlelight 820
CRI (Ra)	80
Wattage (W)	2.3
Product Voltage (V)	230
Average life (Nominal) (h)	15000
Product EAN number	5410288279725

DATA TABLE

General data

Product code	0027972
Product name	TOLEDO™ VINTAGE CANDLE 125LM E27 SL
Technology	LED
Watt (Rated) (W)	2.3
Cap/Base	E27
Fixture rating	Open
General application	Hospitality, Residential & Consumer,

ToLEDo Vintage CANDLE

TOLEDO™ VINTAGE CANDLE 125LM E27 SL

0027972

Operating Temperature Range (°C)	25
Certifications	EUTIE103
ETIM Class	EC001959

Optical data

Luminous flux (lm)	125
Luminous flux (Rated) (lm)	125
Colour temperature (K)	2000
Light colour	Candlelight 820
CRI (Ra)	80
Beam angle (Rated) (°)	360

Electrical data

Wattage (W)	2.3
Starting time (max) (s)	0.5
Warm-up time to 60% of full light (max) (s)	1
Product Voltage (V)	230
Lamp power factor	0.5
No. Of switching cycles before premature failures	50000
Lamp Energy Label (class)	A+
kWh per 1000 hours burning time	3
Nominal Frequency (Hz)	50Hz

Lifetime data

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

Physical data

Nominal Product Length (mm)	93
Nominal Product Diameter (mm)	35
Weight (kg)	0.095

Packaging

Single packaging type	Carton
Product EAN number	5410288279725
Packaging single length (cm)	3.9
Packaging single width (cm)	3.9
Packaging single height (cm)	11.0
DUN14 (inner)	25410288279729
Units per inner package	6
Packaging inner length (cm)	12.0

ToLEDo Vintage CANDLE

TOLEDO™ VINTAGE CANDLE 125LM E27 SL

0027972

Packaging inner width (cm)	8.5
Packaging inner height (cm)	12.5
DUN14 (outer)	15410288279722
Units per outer package	60
Packaging outer length (cm)	45.5
Packaging outer width (cm)	26.6
Packaging outer height (cm)	14.0

Safety data

Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures

PHOTOMETRY

ToLEDo Vintage CANDLE

TOLEDO™ VINTAGE CANDLE 125LM E27 SL

0027972

